



# OX3200-2x3 Unit

3200 CFM Media Filtration System  
3/4 H.P. Direct Drive Fan



The Blue OX3200 unit was developed primarily for larger installations where there is a heavy contamination load and a lot of area to be cleaned. These multi-unit setups have higher filter cloth-to-air ratios, resulting in a significant savings in maintenance and less overall units required. Our 2x3 Units have six times the filter surface area of a single unit, resulting in over three times the filter life. The OX3200 filter systems can be used for any application where contaminates, mist, or smoke is created. Additional unit set-ups, cabinet and filter options available. All units have a Three Year Warranty on all parts besides filters.

Unit Specifications		Technical Specifications	
<b>Air Flow max</b>	3200 CFM	<b>Motor Type</b>	PSC -Direct Drive
<b>Ship Weight</b>	680 lbs	<b>H.P.</b>	3/4 H.P. @60Hz
<b>Hang Weight</b>	650 lbs	<b>Volts</b>	115 V
<b>Dimensions</b>	72"L x 48"W x 72"H	<b>Amps</b>	10.2
<b>Finish</b>	Blue, Brown, Black	<b>Watts</b>	1250 W
<b>Grill/Louver</b>	4-Way Adjustable	<b>Noise Level</b>	62 dBA's @5'



## Accessories

### Included Filters

- (12) 24" x 24" x 4" - 35% Pleated Fiber Pre Filter
- (12) 24" x 24" x 22" - 65% 8 Pocket Bag Filter

### Optional Filters

- 24" x 24" x 4" - Aluminum Mesh Pre-Filter  
Replaces Pleated Filter
- 24" x 24" x 22" - 95% 8 Pocket Bag Filter  
Replaces 65% Bag Filter

### Cabinet Options

- Silencer with Louver  
Reduces sound 6-8 decibels
- Silencer with Grill  
Reduces sound 10-12 decibels
- Magnehelic Pressure Gauge  
Indicates when to change filters
- Strut Channel  
Underside strut for Ceiling Mounting
- Drain Plug  
Oil/Mist application drain via Hose Barb
- Ultraviolet Light Bar Catalyst  
Kills airborne bacteria, mold and Viruses
- Other options including different Motor Voltage available